



Company annual inventory 2011

	Items	Figure		Unit Price in US
01		SDC-435PH <ul style="list-style-type: none"> • 1/3±j Super HAD color CCD • Based on W-V, the latest generation of Winner DSP engine • SSNRIII, Upgraded 2D/3D Noise Reduction technology • Day & Night capability for 24/7 operation • High resolution of 600TV lines • Min. illumination of 0.05Lux@F1.2 (Color) 0.0001Lux@F1.2 (Color sens-up) • Privacy masking with 12 user programmable zones • SSDR (Samsung Super Dynamic Range) • HLC (Highlight Compensation) • DIS (Digital Image Stabilization) • Motion detection • Multi-language OSD • S/N ratio of 52dB • Dual voltage : 24V AC / 12V DC (SDC-435N/P) • Voltage : 12V DC (SDC-435ND/PD), 230V AC (SDC-435PH) 	40 Each	167.00 141.95
02		SCB-2000 <p>Dual (12V DC / 24V AC), 1/3" Super HAD CCD, 600TV lines (Min.), Day & Night, Digital Zoom On / Off (1x ~ 16x)</p>	01 Each	172.00 164.20
03		SDC-313BP <p>1/3" IT color CCD</p> <ul style="list-style-type: none"> - Ultra High Resolution of 530TV lines - 0.3 Lux@F1.2 (color) / 0.002 Lux (Sens-up mode) - Removed noise, ghosting effect with SSNR - White Balance - ATW / AWC / Manual selectable ÆK ~ j (Color Temperature: 1800 ÆK)j10,500 - Privacy image masking with free position - Motion Detection - OSD (On Screen Display) - S/N ratio of 50dB - Power source : 24V AC(N) / 12V DC(P) 	173 Each	116.00 98.60

04		SHC-735PH 24V AC / 12V DC ($\pm 10\%$) 1/3" Vertical double density interline color CCD, Wide Dynamic Range 52Db, Day & Night, Color : 560TV lines	01 Each	267.00 226.95
05		SCC-B1310 1/3" 540 TV Lines Color Camera • 1/3" SONY Super-HAD IT CCD • 540 TV lines • DC12V & AC24V	06 Each	97.00 82.45
06		SCZ-2370 Dual (12V DC / 24V AC) 1/4" Super HA Zoom RatioD CCD 37x (Optical), 16x (Digital) Day & Night Auto (ICR) / Color / B/W / EXT	08 Each	354.00 300.90
07		SOC-4030 Power Source 24V AC 10% / 12V DC 10% compatible 1/3" Super HAD CCD 530TV lines Day & Night On / Auto selectable Motion Detection On / Off (4 Programmable zone, Screen display)	18 Each	202.00 171.70
08		SCO-2120R Dual (12V DC / 24V AC) 1/4" Super HAD CCD Color : 600TV lines Zoom Ratio 12x (Optical), 16x (Digital) Focal Length 3.9 ~ 46mm (F1.67 ~ 1.88) Day & Night Auto (ICR) / Color / B/W IR LED	14 Each	440.00 374.00
09		SCO-2080R Dual (12V DC / 24V AC) 1/3" Super HAD CCD Color : 600TV lines Zoom Ratio 3.6X (Manual) Day & Night Auto (ICR) / Color / B/W Digital Zoom On / Off (1X ~ 16X) IR LED		334.00 283.90
10		SCO-2370P 37x Zoom, IP66, 600TVL, ICR	02 Each	715.00 607.00
11		SIR-4160P W-V, High Resolution D&N IR LED Camera, 0Lux (IR LED On), 600TVL, SSNR3, SSDR, 30m Detection Range with No Light, IP66, Coaxial Communication Support		311.00 264.00

12		SCC-B9372 1/3" 410K/470K pixels Super-HAD CCD• 540(Color)/570(BW) TV lines resolution• Minimum scene illumination : 0 Lux with • IR-LED(42pcs) Focal length & focus externally adjustable• DC iris level external adjustable• Viewable length at night : 45m• Back light compensation• Water resistant (IP66)•) x 129(L)mm ^a Size : 77.5(Φ) AC24V/DC12V : 210mA/650mA (IR LED • On)	24 Each	245.00 208.25
12		SIR-4150P • 1/3± Super HAD color CCD • Built-in 2.5X (3.8 ~ 9.5mm) varifocal lens with auto iris • Built-in high-performance IR LEDs • SSNR digital noise reduction saves DVR storage space • Day & Night with ICR (Infrared Cutoff Filter Removal) • High resolution of 520TV lines (Color), 570TV lines (B/W) • Min. illumination of 0Lux@F1.2 (LED on)) • IP65 Certification • RS-485 remote setup control • S/N ratio of 50dB • Voltage : 12V DC	96 Each	272.00 257.00
13		SCC-B5398B • 1/3" SONY 410K/470K Pixels Super-HAD IT CCD: 600 TV Lines • Day/Night Function (Soft), Sens-Up Function (512x) • Back Light Compensation (Area Setting) • CCVC (Camera Control Via Coaxial cable, Controller : SCX-RD100) • Anti Vandal type, IP-66, Surface type • DC12V & AC24V 60Hz(50Hz)	52 Each	274.00 232.90
15		SCC-B5399 • 1/3" SONY 410K/470K Pixels Super-HAD PS CCD • High Resolution : 600 TV Lines • Wide Dynamic Range(WDR) : NTSC(128x), PAL(160x) • Day/Night Function (ICR), Sens-Up Function (512x) • Privacy Mask Function (Polygonal Mosaic) • Anti Vandal type, IP-66, Surface type • DC12V & AC24V 60Hz(50Hz)		301.00 255.85
16		SCD-2010F • Based on W-V DSP engine • Built-in 3mm/6mm auto iris fixed lens • High resolution of 600TV lines • Min.illumination of 0.04Lux@F1.2 • SSNRIII, coaxial control • Compact, light weight and stylish design	11 Each	195.00 165.75

17		SID-49P <ul style="list-style-type: none"> • 1/3" Super HAD color CCD • Built-in W-IV, the latest generation of Winner DSP engine • Compact, stylish design for various indoor applications • Day & Night capability for 24/7 operation • High resolution of 580TV lines • HLC (Highlight Compensation) • Motion detection (4 zones) • S/N ratio of 52dB • Dual voltage : 24V AC / 12V DC 		188.00
18		SCD-3080P Dual (12V DC/ 24V AC)1/3" Vertical double density interline CCDZoom Ratio3.9x (Manual)Focal Length2.8 ~ 11mm (F1.2)Day &NightAuto (ICR) / Color / B/WColor : 600TV lines (Min.	04 Each	403.00 342.55
19		SCC-B5367P <ul style="list-style-type: none"> • 1/3" SONY 410K/470K Pixels Super-HAD PS CCD • High Resolution : 600 TV Lines • Wide Dynamic Range • Day/Night Function (ICR), Sens-Up Function (512x) • Motion Adaptive Digital Noise Reduction (3D+2D) • Back Light Compensation (Area Setting) • CCVC • DC12V & AC24V 60Hz(50Hz) 		300.00
20		SCC-B5369P <ul style="list-style-type: none"> • 1/3" SONY 410K/470K Pixels Super-HAD PS CCD • High Resolution : 600 TV Lines • Wide Dynamic Range: • Day/Night Function (ICR), Sens-Up Function (512x) • Motion Adaptive Digital Noise Reduction (3D+2D) • Back Light Compensation • Advanced Motion Detection Function DIS (Digital Image Stabilization) • CCVC (Camera Control Via Coaxial cable, Controller : SCX-RD100) • Multi-Language OSD support • DC12V & AC24V 60Hz(50Hz) 		300.00

21		SCP-2120P <ul style="list-style-type: none"> • 1/4± Super HAD CCD • 600TV lines high resolution • 12x optical zoom (3.9 ~ 46mm) • 0.2Lux ultra-low light sensitivity • Features samsung's W-V DSP chipset • 1/4± 600TV lines high resolution • Coax communication support • 360° continuous rotation, high-speed pan & tilt at 650°/s 	00 Each	667.00
22		SIR-60P 12V DC 1/3" Super HAD CCD Color : 580TV lines (Min.) Zoom Ratio Fixed Focal Length 3.6mm Day & Night Auto (ICR) / Color / B/W IR LED 8ea IR Distance 7m (23ft)	05 Each	195.00 165.75
23		SID-50P 12V DC ±10% Image Pick-up Devise 1/3" Super HAD CCD Scanning System 625 Lines / 50 Fields / 25 Frames Resolution 540TV lines Lens Fixed lens f=3mm, D=120° F 2.0 (4, 6, 8mm option)	97 Each	136.00 115.60
24		SNV-3080 2.8~11mm Vari-Focal Lens <ul style="list-style-type: none"> • Fan/Heater built-in for Outdoor Installation • Real-time 30(25)ips at High Resolution(4CIF) • H.264, MPEG-4 & MJPEG Multiple Encoding • Progressive Scan • WDR (Wide Dynamic Range) • Day & Night Function (IR Cut Filter) • Bi-directional Audio Support • SD Memory Slot for Internal Recording • Intelligent Video Analytics • XDR (eXtended Dynamic Range) • Motion Adaptive DNR (Dynamic Noise Reduction) • Privacy Mask (12ea) • DIS (Digital Image Stabilizer)IP66 	01 Each	530.00 450.50
25		SNV-3120 12x optical, 16x digital Zoom <ul style="list-style-type: none"> • High resolution of 4 CIF, 30(25) ips of frame rate • H.264, MPEG-4 & MJPEG Multiple Encoding • Day & Night (ICR), WDR • Built-in SD memory card slot • Digital Noise Reduction 	01 Each	775.00 658.75

26		<p>SCV-2080RP</p> <ul style="list-style-type: none"> • 1/3" Super HAD color CCD • Based on W-V, the latest generation of Winner DSP engine • Built-in 3.6x (2.8 ~ 10mm) varifocal lens with auto iris • Built-in high-performance IR LEDs • SSNRIII, Upgraded 2D/3D noise reduction technology • Day & Night with ICR (Infrared Cutoff Removal) • High resolution of 600TV lines (Color), 700TV lines (B/W) • Min. illumination <ul style="list-style-type: none"> – 0Lux@F1.2 (LED on) – 0.15Lux@F1.2 (Color) – 0.0003Lux@F1.2 (Color sens-up) • Privacy masking with 12 user programmable zones • Protection against water & dust (IP66) • Two types of installation (Flush or surface mount) • SSDR (Samsung Super Dynamic Range) • HLC (Highlight Compensation) • DIS (Digital Image Stabilization) • Motion detection • Coaxial & RS-485 control • 512x sens-up support • Multi-language OSD • S/N ratio of 52dB • Dual voltage : 12V DC / 24V AC 	<p>27 Each</p>	<p>345.00 293.25</p>
27		<p>SPD-2700P</p> <ul style="list-style-type: none"> • Super HAD color CCD ± 1/4" • Based on W-IV, the latest generation of Winner DSP engine • Powerful 27X optical zoom (3.5 ~ 94.5mm) and 12X digital zoom • SSNRII, digital 3D noise reduction technology • Day & Night with ICR (Infrared Cutoff Removal) • High resolution of 550TV lines (Color), 680TV lines (B/W) • Min. illumination of 0.4Lux@F1.6 (Color), 0.02Lux@F1.6 (B/W) • 0.001Lux@F1.6 (Color sens-up) • Privacy masking with 8 programmable zones • HLC (Highlight Compensation) • DIS (Digital Image Stabilization) • Programmable 255 preset positions • Multiple protocol support • Automatic scene tour functions • 1/30 ~ 1/60 sec pan speed and 360° Max. 500° continuous rotation • Motion detection • RS-485/422 remote setup control • Multi-language OSD • S/N ratio of 50dB • Voltage : 24V AC 		<p>983.00</p>






28		SPU-3750TP Dome camera comes with a built-in housing and 37X optical zoom. This premium camera allows accurate monitoring with Intelligent Auto Tracking and forms crystal clear images day and night with a high 550TV lines resolution and ultra low light levels of 0.7Lux.		1,685.00
29		SPU-3700P 37X optical zoom and built-in housing that achieves ultra low light levels of 0.4Lux, forming clear images even in the darkest places. This camera is IP66-rated and is available with a wide selection of accessories for installation versatility indoors or outdoors. • 0.4Lux Ultra-Low Light Levels		1,510.00
30		SCC-C7325P Image 1/4" Super-HAD IT CCD Day/Night Auto / Day / Night (IR Cut Filter) High Speed Shutter NTSC : Yes (1/60~ 1/120,000 sec), PAL : Yes (1/50 ~ 1/120,000 sec) Lens Focal Length / Zoom ratio 3.8mm ~ 38mm / 10x Optical, 10x D-Zoom Remote Control RS-485		755.00
31		SCC-C6437P • 1/4" SONY 410K/470K Pixels Super-HAD IT CCD • 34x Optical & 16x(0.1step) Digital Zoom • High Resolution : 600 TV Lines • Min. illumination 0.0007 Lux (F1.2, 15 IRE, Sens-up 512x, Color) 0.00007 Lux (F1.2, 15 IRE, Sens-up 512x, B/W) • 0~360° Endless Pan, -6~186° Tilting (D-Flip) • Pan/Tilt Speed Min. 0.01°/sec, Max. 600°/sec • Preset 512 ea, Auto Pan 4 ea, Pattern 3 ea • Day Night Function (ICR), Sens-up Function (512x) • Adaptive Digital Noise Reduction (3D + 2D) • Back Light Compensation (Area Setting) • Advanced Motion Detection Function • eXtended Dynamic Range (XDR) • Privacy Mask Function (12ea) • DIS (Digital Image Stabilization) • Time & Day Scheduling • CCVC (Camera Control Via Coaxial cable, Controller : SCX-RD100) • RS-485 (Half/Full)/RS-422 Control (Multi-Protocol support) • Multi-Language OSD (E, F, G, S, I, J, R, P, C, etc) support • Intelligent Video (Moved/Fixed/Fence/Tracking) • Alarm Input 8 ea, Output 4 ea • Operating Temp. : -10 ~ 50°C	04 Each	875.00 743.75

32		SCC-C7437P 1/4" SONY 410K/470K Pixels Super-HAD IT CCD (SCC-C7437) 1/4" SONY 410K/470K Pixels Ex-View HAD PS CCD (SCC-C7439) • 34x Optical & 16x(0.1step) Digital Zoom • High Resolution : 600 TV Lines • Pan/Tilt Speed Min. 0.01°/sec, Max. 600°/sec • Wide Dynamic • Day Night Function (ICR), Sens-up Function (512x)		962.00
33		SCC-C7453P 1/4" SONY 410K/470K Pixels Ex-View HAD PS CCD • 43x(f=3.2~138.5mm) Optical & 16x(0.1step) Digital Zoom • High Resolution : 600 TV Lines • Min. illumination 0.0007 Lux (F1.2, 15 IRE, Sens-up 512x, Color) • 0~360° Endless Pan, -6~186° Tilting (D-Flip) • Wide Dynamic Range (NTSC 128x, PAL 160x) : SCC-C6455 / C7455 • Day Night Function • • Back Light Compensation (Area Setting) • Advanced Motion Detection Function • eXtended Dynamic Range (XDR)		1,300.00
34		SPD-1000P 12V DC (±10%) 1/4" Interline Transfer CCD Zoom Ratio f3.8 ~ 38mm (10X) Color : 520TV lines (Min.	03 Each	632.00 537.20
35		SRD-830D • 8ch DVR • Video (H.264) / Audio (ADPCM) • Up to 120 (NTSC) / 100 (PAL)ips recording rate • Up to 4ch audio inputs and 1ch audio output • Combined BNC and VGA video output for main display (up to 1280 x 1024) • MAX 5 internal HDD (HDD x 5) • HDD & DVD SATA interface • DDNS • Built-in web viewer • DVD R/W • Event notifications by E-mail • PTZ control via Coaxial cable	01 Each	1,040.00 884.00


36		SVR-480D <ul style="list-style-type: none"> • 704 x 480(N) Max Resolution & 120fps(N) Max Recording Speed • Convenient Search & Play Options ?Thumbnail Search (Search quickly with video thumbnails) • Multi-Streaming • Central Management System (CMS) Software • Default Web Viewer • Convenient Control Options(Mouse, PTZ Control & Preset Menus • Default DVD & Simple USB Backup Capacity • Supports 4 channel Audio Recording • Easy to Integrate with any ATM/POS System 	05 Each	755.00 641.75
37		SRD-450 <ul style="list-style-type: none"> Up to 120 (NTSC) / 100 (PAL)fps • recording rate at CIF resolution Full 4CIF resolution recording support• Up to 4ch audio inputs and 1ch audio • outputs Video (H.264) / Audio (G.711)• 		380.00
38		SRD-470D <ul style="list-style-type: none"> • 4ch CIF real-time DVR • Video (H.264) / Audio (ADPCM) • CIF Resolution real-time recording capability • Up to 4ch audio inputs and 1ch audio output • Combined BNC and VGA video output for main display (up to 1280 x 1024)) • HDD & DVD SATA interface • Built-in web viewer • DVD R/W 	03 Each	580.00 493.00
39		SVR-3200 <p>32 Composite video 0.5-2 Vpp Resolution NTSC : 704 x 480 / PAL : 704 x 576 Up to 16TB using external storage option Up to 4 SATA HDDs Up to 2 expansion bay DVD-R / CD-R 2 External USB ports BMP, AVI, Proprietary format / JPEG (Exclusive viewer) Password Protection VGA Analog RGB 800 x 600, 1024 x 768, 1280 x 1024 resolution (SVR-3200 : 2 VGA) Alarm</p>	01 Each	4,340.00 3,689.00
40		SVR-1670 <p>16 composite video 0.5-2 Vpp, 75 ohm automatic termination NTSC : 704 x 480 PAL : 704 x 576 Manual, Schedule, Event, Emergency overwrite Modes Continuous Up to 16TB using external storage option Up to 4 SATA HDDs 2 External USB Ports File Format (Back up) AVI, Proprietary format (Include viewer) / JPEG (CMS)</p>	05 Each	1,475.00 1,253.00

41		SRD-1610D <ul style="list-style-type: none"> • 16ch DVR • Video (H.264) / Audio (ADPCM) • Up to 120 (NTSC) / 100 (PAL)ips recording rate • Up to 4ch audio inputs and 1ch audio output • Combined BNC and VGA video output for main display (up to 1280 x 1024) • SRD-1610 : MAX 6 internal HDD (HDD x 6) SRD-1610D : MAX 5 internal HDD (HDD x 5) • HDD & DVD SATA interface • DDNS • Built-in web viewer • DVD R/W (SRD-1610D) • Event notifications by E-mail 	04 Each	1,475.00 1,253.00
42		SVR-945 The SVR-945 is a compact and affordably priced 9 channels DVR that can record high quality images in real time with highly efficient advanced MPEG-4 compression. It is equipped with a wide range of smart functions for user convenience and system reliability such as thumbnail search modes, ATM/POS text recording, and easy control with intuitive GUI and mouse interfaces. Designed as a compact yet feature-rich solutions, it can easily and conveniently be installed in virtually any location.		1,351.00 1,148.35
43		SHR-6162 <ul style="list-style-type: none"> • 16CH DVR • Video (MPEG-4) / Audio(ADPCM) • Up to 120(NTSC)/100(PAL) IPS Recording Rate • Up to 4Ch Audio Inputs and 1Ch Audio Output • Combined BNC and VGA Video Output for main display (up to 1280x1024) • MAX 5 Internal HDD (HDDx5) • HDD & DVD SATA Interface • DDNS • Built-in Web viewer • Event Notifications by E-mail • DVD R/W 	01 Each	1,475.00 1,253.00
44		SVR-960CN <ul style="list-style-type: none"> • True real-time 270fps(N), 225fps(P) digital image display 270fps(N), 225fps(P) digital video recording • MPEG-4 Compression • High resolution image • Capacity for up to 2 Internal SATA HDDs • Two front panel USB ports • DVD writer • ATM/POS transaction data recording and search • 3 Multi-monitor • Built-in web server • 9 Channels audio recording • Coaxial Control 	01 Each	1,615.00 1,372.75

45		SVR-480 <ul style="list-style-type: none"> • 704 x 480(N) Max Resolution & 120fps(N) Max Recording Speed Convenient Search & Play Options Multi-Streaming Central Management System (CMS) Software Default Web Viewer Convenient Control Options(Mouse, Remote Controller, Keyboard Controller) • PTZ Control & Preset Menus • Default DVD & Simple USB Backup Capacity Recording • Easy to Integrate with any ATM/POS System • Multiple Language OSD• Supports 4 channel Audio 		755.00 641.75
46		SVR-470 <p>4 Channel DVR</p> <ul style="list-style-type: none"> • Self-contained front LCD for easy monitoring • H.264 high performance image compression • 4 channels & 120fps real-time recording • 320GB high storage capacity • Excellent Remote Network Transfer • Various Digital Features like User Friendly GUI, Front USB for Convenient Back up 	01 Each	565.00 480.25
47		SVS-5E <p>HDD Extension Unit</p> <ul style="list-style-type: none"> • 1U 19-inch rack case • Data transfer speed : Up to 3.0Gbps (SATA II) • Available STA HDD : Up to 4 (4TB) • Expandable for more storage 	02 Each	1,300.00 1,105.00
48		SCC-1000 <p>LCD Display 16 x 2 Character LCD</p> <p>Joystick (3-axis Twist Zoom)</p> <p>Samsung Techwin PTZ Dome PELCO-D/P, Panasonic, Vicon, AD, Honeywell, Samsung Electronics Zoom Camera SDZ-375/370 Receiver SRX-100B Up to 255 Cameras (Suitable for Mid-, Large-size System) RS-485 / RS-422 (Remote Control: 1km or Longer Distance) Transfer Speed 2,400 ~ 57,600bps 12V DC, 140mA</p>	04 Each	300.00 255.00

49		SSC-5000 <ul style="list-style-type: none"> • Dome camera & DVR control • 4.3" TFT color LCD touch panel • 3D joystick (pan / tilt / zoom control) • Jog shuttle (DVR playback control) • Pan/tilt & lens control (iris, focus, zoom) • Multiple camera protocol support • 2 ports RS-485 control interface • USB 2.0 interface for S/W upgrade 	01 Each	880.00 748.00
50		SCC-3100A 12V DC, 700mA Connector LCD Display 20 x 4 Character LCD Control SPD-3300/3000/2500/2300/2200/1600 PTZ Dome PELCO-D, PANASONIC (WV-CS854) Control SAMSUNG ELECTRONICS (SCC-643/641) DVR SVR-1650/1640/1630/950/440/430 Receiver SRX-100B Matrix SMX-25632 Control Quantity Max. 255 Auto Surveillance Tour, Group, Swing, Preset etc. Selection of PTZ, DVR : Each ID input	03 Each	878.00 746.30
51		SCC-101 Zoom & OSD Controller	16 Each	27.00 23.00
52		SAL-12240 C-mount 20X(f \pm 1/2 12~240mm) Motorized Zoom Lens	01 Each	1,810.00 1,538.50
53		SLA-3580DN 1/3" Varifocal Lens f 3.5~8 mm		50.00
54		SLA-M2882 \pm CS-mount Megapixel 1/3 Varifocal Lens F1.4 2.8 ~ 8.2mm	51 Each	115.00

55		SLA-550D 1/3" Varifocal Lens f 5~50 mm		78.00
56		SSA-S3011 Total Users 10,000 / 20,000 Users (Selectable) Fingerprint Users 1,000 Fingerprint Templates Size 800 Bytes for 2 fingerprint Templates Event Buffer 20,000 / 10,000 Event Buffers (Selectable) Power / Current DC 12V / Max.540mA	01 Each	1,350.00 1,147.50
57		SSA-S2101 13.56MHZ Proximity Card Reader	04 Each	740.00 629.00
58		SSA-S2000 Standalone 125KHz Proximity & PIN Single Door Access controller <ul style="list-style-type: none"> • 512 Users • 1ea of External Reader Port for Exit : 26bit Wiegand • All I/Os and Operation Time Programmable by Keypad • Independent 5 Inputs and 4 Outputs including 2ea of 2 Form-C Repay Outputs • Keypad Lock by Try-out Error Alarm Function • Duress Mode Function • Toggle Mode for Door Opening / Closing • Safe (default) / Secure Mode available • Lock Control by Door Sensor • Dual Tamper Switches • Chime Bell Output • 26bit Wiegand Output for Reader Mode 	04 Each	280.00 283.00
59		SSA-S1000 <ul style="list-style-type: none"> • Standalone 125KHz Proximity Access Controller • 512 Users • Direct Control of Door Lock • Power Fail Safe or Power Fail Secure Locks selectable • Solid Epoxy Potted • Weatherproof 	04 Each	240.00 204.00

60		SSA-R2011		905.00
61		SSA-C200 • ISO Credit Card Size and Thickness	400 Each	05.50
62		SSA-X500 FingerPrint Scanner Compact and elegant design, which is more convenient to use – Excellent product durability that assures a long life – Provides USB interface		250.00
63		SMX-400ST Stand for SMT-3222 and SMT-4022		34.00
64		SMT-3222P Screen Size 32" Resolution (HxV) 1366 x 768 Response Time (ms) 8 (G-to-G) Horizontal Resolution 600TV Lines Input Video 1 composite(RCA), 1 HDMI Interface PC 1 RGB (D-sub), 1 DVI, 1 RS-232 Audio 2 RCA		1,278.00
65		SMT-4022P Screen Size 40" Resolution (HxV) 1920 x 1080 600TV Lines Comb Filter 3D Speaker Output 20W (10W x 2 built-in) Input Video 1 composite(RCA), 1 HDMI Interface PC 1 RGB (D-sub), 1 DVI, 1 RS-232 Audio 2 RCA		1,752.00
66		SMT-1922 • Ultra high resolution 620 TV lines for the PAL version* • Superior image quality DNle • High contrast ratio 1000:1 • Fast response time 5ms • Durable tempered glass screen • Support up to 1280 x 1024 resolution • Height adjustable and swiveling stand for desktop • Built-in speakers • Support vesa(R)-compliant mounting solution * 600 TV Lines for the NTSC Version		525.00

67		STB-270PWV Wall Mount		44.00
68		STB-280PW Wall Mount		55.00
69		SCX-301WMW	06 Each	53.00 45.00
70		SADT-732CM Ceiling Mount (SCC-C7325 / SNC-7325)	06 Each	44.00 37.40
71		SCX-300WM Wall Mount (SCC-C7453/C7455, SCC-C6453/C6455 with SCX-300HM)	30 Each	44.00 37.40
72		STB-249VWS Vandal Dome Wall Bracket Silver Model : STB-249VWS Ivory Model : STB-249VW	05 Each	40.00 34.00
73		SADT-732WM Wall Mount (SCC-C7325 / SNC-7325)		44.00
74		STB-30PF Ceiling Flange	02 Each	22.00 18.70
75		STB-270B <ul style="list-style-type: none"> • Operating Temperature : -20\pmEC ~ 50\pmEC • Operating Humidity : 0 to 90% RH • Antivibration / Waterproof : IP 66 • Dimensions (WxH) : 182 x 218 x 92.5mm(7.17"x8.58"x3.64") • Weight : 2.98Kg (6.57 lb) 	05 Each	45.00 38.25

76		STB-400 Indoor/Outdoor Housing Bracket	20 Each	27.00 23.00
77		STB-4150V Bracket for Fixed Camera	22 Each	16 13.50
78		SCX-300CM <ul style="list-style-type: none"> • Ceiling mount adaptor • Indoor/outdoor use • Aluminium material • Applicable camera : SCC-C7437/C7439, SCC-C7453,C7455 • Applicable cameras with using SCX-300HM : SCC-C6437/C6439, SCC-C6453/C6455 		44.00 37.40
79		SCX-300PM <ul style="list-style-type: none"> • Pole mount adaptor for SCX-300WM • Indoor/outdoor use • Steel material 	07 Each	44.00 37.40
80		STB-300PW Wall Mount for PTZ Dome Camera (SPU-3750T/3700)		34.00
81		SCX-300KM <ul style="list-style-type: none"> • Corner mount adaptor for SCX-300WM • Indoor/outdoor use • Steel material 	11 Each	44.00 37.40
82		STB-40PF Ceiling Flange (SPU-3750T/3700)	03 Each	16.00 13.60

83		STB-355PP Can be used with STB-30PF PTZ Dome Parapet Mount	02 Each	337.00 286.45
84		STH-500H Outdoor Housing(STH-500H)		123.00
85		STH-600H The STH-600/600H are all-weather housings for indoor and outdoor use which protect a camera from external stimulation such as dust, moisture, temperature, or impact. The STH-600H comes with a built-in fan/heater that offers stable operation environment of CCTV cameras. The housings provide excellent installation convenience along with beautiful design.	20 Each	176.00 149.60
86		SHB-4300H For fixed camera application Aluminum diecasting construction• Fully cable managed bracket• De-mister heater, fan• Support three cable glands• 24V AC•	15 Each	
87		STB-370PC PTZ Dome Ceiling Flange (SPD-3750/3750T/3700/3700T/3350/3310/2700)	19 Each	88.00 74.80
88		STB-249PWV	05 Each	39.00 33.00
89		SSA-X100 <ul style="list-style-type: none"> • Power package for control panel (1 PSU) • Input : 90~250V AC, 50/60Hz, Max 1.2A • Output : 13.5V DC, 3.0A • Communication status via LED indicator • Surge protection (NFB) • Low battery check • AC power failure check • Battery recharge circuit 	02 Each	300.00 255